



## IE Series

High Frequency Internal Vibrators




### Simply effective: the IE-Series

The internal vibrators of the IE-Series from Wacker Neuson are equipped with a high-frequency electric motor. They provide excellent concrete compaction results. At the same time, the user benefits from the ergonomically designed housing which provides a comfortable and user friendly handling.

- Attractive price- performance ratio
- Robust design
- Ideal ergonomics for easy handling
- Internal vibrators available in three sizes of vibrator heads
- High-frequency electric motor for optimum compaction results

Vibrator head sizes:  
three diameter sizes available: 38, 45 und 58 mm





## Technical specifications

	<b>IE38</b>	<b>IE45</b>	<b>IE58</b>
Diameter of the vibrator head mm	38	45	58
Length of the vibrator head mm	285	320	327
Weight kg	10.4	12.3	14.3
Protective hose length max.* m	10	10	10
Effective diameter ** cm	38	45	58
Vibrations rpm	12,000	12,000	12,000
Engine / Motor ***	Asynchronous motor	Asynchronous motor	Asynchronous motor
Voltage V	42	42	42
Current A	5	8	12
Frequency Hz	200	200	200
Power cable m	15	15	15

\* Standard hose length 5 und 10 m. Special order of shorter length possible. \*\* This is non-binding information, based on the practical experience of our clients under certain operating conditions. Please note that under specific operating conditions these findings may vary. We recommend that you always perform a test pouring under the operating conditions. \*\*\* Ideally suited for use with a Wacker Neuson frequency and voltage converter.

### Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.