



KTU 2

Portable Frequency Converter



The first converter with integrated cable drum

25 metres of cable and the low weight mean that the converter KTU is extremely flexible deployable. That also applies for use with the cable completely rolled up. This converter always performs to the full, thanks to its optimal cable diameter, high-quality electronics und active cooling system. And its robust design ensures long-lasting performance & reliability. The intelligent voltage and power management is particularly practical. It compensates for fluctuations of mains input voltage, wrongly dimensioned extensions or appliances with greatly varying use of power. It offers optimum protection to all connected appliances.

- Maximum safety: Galvanic isolation with isolating transformer
- Maintenance-free
- Shock and moisture resistant sealed electronics
- Intelligent voltage and power management



Technical specifications

L x W x H	387 x 395 x 446 mm
Weight	34.4 kg
Input voltage 1~	230 V
Output voltage 3~	250 V
Input frequency	50 - 60 Hz
Output frequency	200 Hz
Input current	13 A
Output current	35 A
Input performance	3 kVA
Output performance	2.6 kVA
Protection class	IP 44
Power cable	25 m

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.