

The rugged PA 'F' series breakers offer models that accomplish all hand breaker operations through the matching of weight and power. All major components are made from traditional alloy steel drop forgings

All model incorporate:

- Built in lubricator
- Swivel air condition
- Reinforced throttle control and rubber grips, combining with low vibration to give maximum operator comfort.
- Foot operated latch retainer allowing steels to be easily and quickly changed.
- Standard models are silenced with a high impact reinforced silencer for a trouble-free low-noise Output.

## PA21F RANGE

A lightweight breaker for concrete breaking, asphalt cutting and general work with an excellent power-toweight ratio.

## PA28F RANGE

The general purpose contractor's tool suitable for most breaking and jobbing work.

## **PA39F RANGE**

A heavy duty breaker for sustained demolition work.

## **BREAKER STEELS**

Full range of quality Breaker steels available.



<b>TECHNICAL SPECIFICATION</b>												
MODEL	Sile	IGHT enced (Kgs)	WEIGHT Unsilenced Lbs (Kgs)	LENGTH Ins (mm)	BORE Ins (mm)	STROKE Ins (mm)	BLOWS PER MINUTE Hz	CONSUM @96p.s.i CFM (			K SIZE (mm)	HOSE FITTING ins
PA21FS	46	(21)	43 (19.5)	24.6 (625)	2.25 (57)	5.00 (125)	1250 (21)	30	(19)	1 1/8 1 1/4	(28) (32)	3/4NPT
PA28FS	70	(32)	65 (29.5)	25.5 (650)	2.25 (57)	5.75 (146)	1250 (21)	65	(30)	1 1/8 1 1/4	(28) (32)	3/4NPT
PA39FS	95	(43)	90 (41.0)	29.0 (737)	2.25 (57)	7.50 (190)	1000 (17)	75	(35)	1 1/8 1 1/4	(28) (32)	3/4NPT

Standard Models are silenced, Unsilenced versions are available