

## S9000 230V 50HZ

### THE COMPLETE DIESEL PACKAGE



Showing the excellence of Pramac's professional equipment, this generator offers a robust package with a modern and economical Diesel engine. Perfect for intensive use, it's equipped with a control panel which allows to integrate many accessories and options for better comfort and for optimal command.

#### Main Features

Frequency	Hz	50
Voltage	V	230
Power factor	cos $\phi$	0.9
Phase and connection		1

#### Power Rating

Standby power LTP	kVA	8.8
Standby power LTP	kW	7.9
Continuous power COP	kVA	7.6
Continuous power COP	kW	6.8

#### Ratings definition (According to standard ISO8528 1:2005)

**COP** - Continuous Power: It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.

**LTP** - Limited-Time running Power: It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

### Engine specifications

Engine manufacturer		Lombardini
Model		25LD330
Engine cooling system		Air
Displacement	cm <sup>3</sup>	654
Aspiration		Natural
Operating Speed-Nominal	rpm	3000
Speed governor		Mechanical
Fuel		Diesel
Oil capacity	l	1.8
Starting system		Electric
Electric circuit	V	12



### Alternator Specifications

Class		H
IP protection		23
Poles		2
Frequency	Hz	50

### Dimensional data

Length	(L) mm	960
Width	(W) mm	641
Height	(H) mm	667
Dry weight	Kg	157
Fuel tank capacity	l	24

### Autonomy

Fuel consumption @ 75% PRP	l/h	2.17
Fuel consumption @ 100% PRP	l/h	2.91
Running time @ 75% PRP	h	11.06
Running time @ 100% PRP	h	8.25

## GENSET CONTROL PANEL

Mounted on the genset and complete of: instrumentation, control, protection of the generating set and sockets.



### COMMANDS

- Start selector switch with key: OFF - ON - START

### INSTRUMENTATION

- Oil Pressure indicator

### PROTECTIONS

- Thermal breaker
- Low oil pressure

### SOCKET TYPE

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 32A IP44	1

## ACCESSORIES

### TRANSPORTATION KIT

- With fix handles
- With folding handles



### LIGHT TOWER

for portable generators (with tubular frames)

- Maximum Height 4.2m
- Elevations Pneumatic
- Quick open/close systems for legs
- Mast support and four lifting
- Lamp available Watt/Type:
  - n.4 X 500W Halogen (required power from generator: 2.5kVA 230V Single Phase)
  - n.4 X 1000W Halogen (required power from generator: 5,0kVA 230V Single Phase)



### MTS- MANUAL TRANSFER SWITCH

- Manual transfer switch 40A (for manual control versions 230V)



Printed on 3/11/2015 (ID 2479)

©2012 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice | ENERGY GENERATION is registered trademarks of PR INDUSTRIAL s.r.l. Other company, product or service names may be trademarks or service marks of others. RevA (06/2012).

